

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | | |
|-----------------|------|--|
| Model #: | | |
| Item #: | Qty: | |
| Available W/H : | | |
| Approval : | | |

Undercounter Freezer - Drawers

Undercounters PRO Series

Model: PUF-48-D4-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



= FEATURES & BENEFITS =

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

- Digital temperature control & monitor system
 - Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.
- Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a **22 gauge** stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Magnetic drawer gaskets

Magnetic drawer gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.

- Freezer holds -10°F ~ 0°F for the best in frozen food preservation
- Lifetime guaranteed heavy duty handles
- Built to maintain NSF standard temperatures in 100°F ambient
- 4 week lead time applies













| | | | | | | | intervent interve | ж |
|-------------|----------------|---------|---------|----------------|-----|------|-------------------------|---------------------------------|
| Model | Swing Doors | Drawers | CU./FT. | #of Shelves | НР | AMPS | Crated Weight (lbs.) | L x D*x H [†] (inches) |
| PUF-48-D4-N | - | 4 | 12.2 | - | 1/2 | 8.0 | 320 | 481/4 x 30 x 30 |

(unit: inch)

Model: PUF-48-D4-N

| ELECTRICAL DATA | | | | | | |
|----------------------------|----------------|--|--|--|--|--|
| Voltage | 115/60/1 | | | | | |
| Plug Type | ① NEMA 5-15P | | | | | |
| Full Load Amperes | 8.0 | | | | | |
| Compressor HP | 1/2 | | | | | |
| Cord Length (ft.) | 10 | | | | | |
| Refrigerant | R-290 | | | | | |
| DIMENSIONAL DATA | | | | | | |
| Net Capacity (cu. ft.) | 12.2 | | | | | |
| Ext. Length Overall (in.) | 481/4 (1226mm) | | | | | |
| Ext. Depth Overall (in.)* | 30 (762mm) | | | | | |
| Ext. Height Overall (in.)† | 30 (762mm) | | | | | |
| # of Doors | - | | | | | |
| # of Drawers | 4 | | | | | |
| # of Shelves | - | | | | | |
| Net Weight (lbs.) | 245 | | | | | |
| Gross Weight (lbs.) | 320 | | | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- 4 week lead time applies


OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- · Stainless steel double overshelf: TSOS-4R
- Back splash guard: TU-48B
- ** Please allow lead time for shipping. Please call factory for more details to place an order.

PLAN VIEW



TOP VIEW



SIDE VIEW

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002

Ver.20191101





















^{*} Depth does not include 2" for door handle & rear spacers.

[†] Height does not include 5-3/8" for caster height.