

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Undercounter Refrigerator - Shallow Depth

Undercounters M3 Series

Model: MUR-34S-N6



== FEATURES & BENEFITS ==_

- Digital temperature control & monitor system Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.
- Hydrocarbon refrigerants (R-600a)
 With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- Stainless steel exterior The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. The M3 model

adds a touch of style to the most refined setting.

■ High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Ergonomically designed doors

maintaining the cool inner temperature.

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

- LED interior lighting & fan control Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 38°F for the best in food preservation













Model MUR-34S-N6	Doors	4.27	Shelves	1/5	2.6	Weight (lbs.) 161	(inches) 34 x 221/2 x 255/8
Model	Swing	CII/FT	#of	ПР	АМРС	Crated Weight (the)	L x D*x H†

Model: MUR-34S-N6

ELECTRICAL DATA	ECTRICAL DATA			
Voltage	115/60/1			
Plug Type	NEMA 5-15P			
Full Load Amperes	2.6			
Compressor HP	1/5			
Cord Length (ft.)	9			
Refrigerant	R-600a			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	4.27			
Ext. Length Overall (in.)	34 (864mm)			
Ext. Depth Overall (in.)*	221/2 (570mm)			
Ext. Height Overall (in.)†	255/8 (650mm)			
# of Doors	2			
# of Shelves	2			
Shelf Size (L x D) (in.)	141/4 x 111/8			
Net Weight (lbs.)	150			
Gross Weight (lbs.)	161			

Design and specifications subject to change without notice

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 3/4" for rear spacers.

† Height does not include 5" for caster height.

5 Year Parts and Labor Warranty 7 Year Compressor Warranty

STANDARD FEATURES


- · Anti-corrosion coated evaporator
- · Self-contained system
- 4" dia. swivel casters with locks on the front set
- ** Lead time applies. Please contact your sales representative for more details to order.

OPTIONAL ACCESSORIES


- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, ½" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600

PLAN VIEW





TOP VIEW



SIDE VIEW

NATURAL











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









Ver.20230929