

REFRIGERATOR MANUFACTURER Turbo air more durable, efficient, beautiful	4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com		Project:
			Model #:
			Item #:
	Available W/H:	Qty:	
	Approval:		
	AIA #:	SIS #:	
			CSI Section 11400

Pass Thru Half Glass Door Heated Cabinet

Pass-Thru
PRO Series

FEATURES & BENEFITS

- **Digital temperature control & monitor system**
 - Keeps food products safe by maintaining constant temperatures
 - Alarm beeps when doors are not sealed
 - Early warning alarm program detects issues before malfunction occurs
 - Digital display allows for easy monitoring
 - Sensitive touch display
- **Ducted fan air distribution system**
Maintains temperature within the food zone
- **On/Off switch**
ON/OFF switch is located on control panel
- **All stainless steel cabinet construction**
The PRO series model boasts a stainless steel interior and a **22 gauge** stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.
- **Sturdy, clean stainless steel shelving**
Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.
- **LED interior lighting**
Includes a U.S. patented dimming option, exclusively from Turbo Air. This feature reduces energy consumption by 3~5%.
- **High-density polyurethane insulation**
The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- **Half length glass doors with locks**
- **Self-closing doors with stay open feature at 120 degrees**
- **Heated cabinet holds 140°F ~ 180°F for the best in food preservation**
- **Lifetime guaranteed heavy duty hinges and handles**
 - PRO-26-2H-G-PT: Right hinged, 115V
 - PRO-26-2H-G-PT-L: Left hinged, 115V
 - PRO-26-2H-G-PT-LR: Front left hinged, back right hinged, 115V
 - PRO-26-2H-G-PT-RL: Front right hinged, back left hinged, 115V
 - PRO-26-2H2-G-PT: Right hinged, 208V
 - PRO-26-2H2-G-PT-L: Left hinged, 208V
 - PRO-26-2H2-G-PT-LR: Front left hinged, back right hinged, 208V
 - PRO-26-2H2-G-PT-RL: Front right hinged, back left hinged, 208V

Model : PRO-26-2H-G-PT(-L)(-LR)(-RL)
PRO-26-2H2-G-PT(-L)(-LR)(-RL)





Model	Swing Door	CU./FT.	#of Shelves	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D* x H† (inches)
PRO-26-2H-G-PT(-L)(-LR)(-RL) PRO-26-2H2-G-PT(-L)(-LR)(-RL)	4	28	3	1550	13.5 7.5	366	28 3/4 x 36 1/4 x 78

Pass Thru Half Glass Door Heated Cabinet

Pass-Thru
PRO Series

Model : PRO-26-2H-G-PT(-L)(-LR)(-RL) PRO-26-2H2-G-PT(-L)(-LR)(-RL)

ELECTRICAL DATA	PRO-26-2H-G-PT (-L)(-LR)(-RL)	PRO-26-2H2-G-PT (-L)(-LR)(-RL)
Voltage	115/60/1	208/115/60/1
Plug Type	 NEMA 5-15P	 NEMA L14-20P
Full Load Amperes	13.5	7.5
Wattage (W)	1550	1550
Cord Length (ft.)	8	8
DIMENSIONAL DATA		
# of Doors	4	4
# of Racks Accepted	1	1
Net Capacity (cu. ft.)	28	28
Ext. Length Overall (in.)	28 3/4 (730mm)	28 3/4 (730mm)
Ext. Depth Overall (in.)	36 1/4 (920mm)	36 1/4 (920mm)
Ext. Height Overall (in.)†	78 (1982mm)	78 (1982mm)
Int. Length Overall (in.)	22 (559mm)	22 (559mm)
Int. Depth Overall (in.)	27 5/8 (702mm)	27 5/8 (702mm)
Int. Height Overall (in.)	58 3/4 (1493mm)	58 3/4 (1493mm)
# of Shelves	3	3
Shelf Size (L x D) (in.)	23 1/2 x 26 3/8	23 1/2 x 26 3/8
Net Weight (lbs.)	321	321
Gross Weight (lbs.)	366	366

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2-1/2" for door handles.

† Height does not include 5" for caster height.

■ WARRANTY : 3 Year Parts and Labor Warranty

■ STANDARD FEATURES


- **Door locks**
- **4" dia. swivel casters with locks on the front set**
- **Easy replaceable one piece magnetic door gaskets**
- **Solid and sturdy grille design**

■ OPTIONAL ACCESSORIES


- 5" caster, 1/2" diameter & 13 TPI:
M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: H26R901680
- Half door bun tray rack: TSP-2224
(each holds up to six 18"L x 26"D sheet pans-sold separately)
- Tray slides kits: TS1-N1(#1), TS1-N4(#4), TS1-UN(Universal), TS1-N1 HALF, TS1-N4 HALF, TS1-UN HALF
- (1) Pair of #1 Tray Slides: H26R104460
- (1) Pair of Universal Tray Slides: H26R104470

PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

Ver.20230126



- Turbo Air : 800-627-0032 ■ GK : 800-500-3519
- Warranty : 800-381-7770 ■ AC : 888-900-1002

REFRIGERATOR MANUFACTURER
Turbo air

REFRIGERATOR MANUFACTURER
GERMAN KNIFE

REFRIGERATOR MANUFACTURER
RADIANCE

REFRIGERATOR MANUFACTURER
Turbo air TEXAKING

Continued product development may necessitate specification changes without notice.