

<div><div>REFRIGERATOR MANUFACTURER</div><div><div>Turbo air</div><div>more durable, efficient, beautiful</div></div></div>	<div>4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com</div>	Project:	
		Model #:	
		Item #:	
		Available W/H:	Qty:
		Approval:	
		AIA #:	SIS #:
		CSI Section 11400	

Pass Thru Half Glass & Solid Door Heated Cabinet

Pass-Thru
PRO Series

FEATURES & BENEFITS

■ Digital temperature control & monitor system

- Keeps food products safe by maintaining constant temperatures
- Alarm beeps when doors are not sealed
- Early warning alarm program detects issues before malfunction occurs
- Digital display allows for easy monitoring
- Sensitive touch display

■ Ducted fan air distribution system

Maintains temperature within the food zone

■ On/Off switch

ON/OFF switch is located on control panel

■ All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a **22 gauge** stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

■ Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ LED interior lighting

Includes a U.S. patented dimming option, exclusively from Turbo Air. This feature reduces energy consumption by 3~5%.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Half length glass doors with locks

■ Self-closing doors with stay open feature at 120 degrees

■ Heated cabinet holds 140°F ~ 180°F for the best in food preservation

■ Lifetime guaranteed heavy duty hinges and handles

- PRO-26-2H-GS-PT: (Front) Glass + (Back) Solid door, Right hinged, 115V
- PRO-26-2H-GS-PT-L: (Front) Glass + (Back) Solid door, Left hinged, 115V
- PRO-26-2H-GS-PT-LR: (Front) Glass left hinged + (Back) Solid door right hinged, 115V
- PRO-26-2H-GS-PT-RL: (Front) Glass right hinged + (Back) Solid door left hinged, 115V
- PRO-26-2H2-GS-PT: (Front) Glass + (Back) Solid door, Right hinged, 208V
- PRO-26-2H2-GS-PT-L: (Front) Glass + (Back) Solid door, Left hinged, 208V
- PRO-26-2H2-GS-PT-LR: (Front) Glass left hinged + (Back) Solid door right hinged, 208V
- PRO-26-2H2-GS-PT-RL: (Front) Glass right hinged + (Back) Solid door left hinged, 208V



Model	Swing Doors	CU./FT.	#of Shelves	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D x H [†] (inches)
PRO-26-2H-GS-PT(-L)(-LR)(-RL) PRO-26-2H2-GS-PT(-L)(-LR)(-RL)	4	27	3	1550	13.5 7.5	342	28 ³ / ₄ x 36 ¹ / ₄ x 78

Model : PRO-26-2H-GS-PT(-L)(-LR)(-RL) PRO-26-2H2-GS-PT(-L)(-LR)(-RL)

ELECTRICAL DATA	PRO-26-2H-GS-PT (-L)(-LR)(-RL)	PRO-26-2H2-GS-PT (-L)(-LR)(-RL)
Voltage	115/60/1	208/115/60/1
Plug Type	NEMA 5-15P	NEMA L14-20P
Full Load Amperes	13.5	7.5
Wattage (W)	1550	1550
Cord Length (ft.)	8	8
DIMENSIONAL DATA		
# of Doors	4	4
# of Racks Accepted	1	1
Net Capacity (cu. ft.)	27	27
Ext. Length Overall (in.)	28 3/4 (730mm)	28 3/4 (730mm)
Ext. Depth Overall (in.)*	36 1/4 (920mm)	36 1/4 (920mm)
Ext. Height Overall (in.)†	78 (1982mm)	78 (1982mm)
Int. Length Overall (in.)	22 (559mm)	22 (559mm)
Int. Depth Overall (in.)	27 5/8 (702mm)	27 5/8 (702mm)
Int. Height Overall (in.)	58 3/4 (1493mm)	58 3/4 (1493mm)
# of Shelves	3	3
Shelf Size (L x D) (in.)	23 1/2 x 26 3/8	23 1/2 x 26 3/8
Net Weight (lbs.)	297	297
Gross Weight (lbs.)	342	342

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2-1/2" for door handles.

† Height does not include 5" for caster height.

■ WARRANTY : 3 Year Parts and Labor Warranty

■ STANDARD FEATURES


- Door locks
- 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- Solid and sturdy grille design

■ OPTIONAL ACCESSORIES


- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: H26R901680
- Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans-sold separately)
- Tray slides kits: TS1-N1(#1), TS1-N4(#4), TS1-UN(Universal), TS1-N1 HALF, TS1-N4 HALF, TS1-UN HALF
- (1) Pair of #1 Tray Slides: H26R104460
- (1) Pair of Universal Tray Slides: H26R104470

PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

Ver.20230126



- Turbo Air : 800-627-0032 ■ GK : 800-500-3519
- Warranty : 800-381-7770 ■ AC : 888-900-1002

Refrigerator Manufacturer
Turbo air

German
KNIFE

IRADIANCE

Refrigeration System
Turbo air

Texaking

Continued product development may necessitate specification changes without notice.