

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

	Qty:
SIS #:	
	SIS #:

Mega Top Unit



Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a 22 gauge stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. Only the PRO series uniquely provides stainless steel shelving.

- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

LED interior lighting & fan control Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.


- Spring assisted heavy duty gravity hinge
- Easy, removal hood & hood lid for cleaning

Model : PST-28-12-N **PST-28-12-N-L**

Food Prep Tables **PRO** Series



Patented Self-Cleaning Condenser



- Insulated hood & hood lid
- Refrigerator holds 33°F ~ 39°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles
- Built to maintain NSF standard temperatures in 100°F ambient
- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail

- PST-28-12-N: Right hinged door
- PST-28-12-N-L: Left hinged door

						NATURAL Refrigeran	Intertek	U. S. A
Model	Swing Doors	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	$L \underset{(inches)}{x} D^{*} x H^{\dagger}$
PST-28-12-N(-L)	1	8	1	12	1/6	6.6	220	271/2 x 34 x 391/8

Ver 20230112 Printed in U.S.A.

* Depth does not include 3" for cutting board and 1" for rear spacers. † Height does not include 5" for caster height.

Mega Top Unit

Model : PST-28-12-N(-L)

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	NEMA 5-15P				
Full Load Amperes	6.6				
Compressor HP	1/6				
Cord Length (ft.)	10				
Refrigerant	R-290				
DIMENSIONAL DATA					
Ext. Length Overall (in.)	271/2 (700mm)				
Ext. Depth Overall (in.)*	34 (864mm)				
Ext. Height Overall (in.) [†]	391/8 (993mm)				
# of Doors	1				
# of Shelves	1				
# of Pans	12				
# of Hood	1				
Net Capacity (cu. ft.)	8				
Shelf Size (L x D) (in.)	221/2 x 17				
Net Weight (lbs.)	216				
Gross Weight (lbs.)	220				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

Depth does not include 3" for cutting board and 1" for rear spacers.

+ Height does not include 5" for caster height.

WARRANTY: 5 Year Parts and Labor Warranty 7 Year Compressor Warranty

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included
- # Accommodates 1/6 size, 6" deep condiment pans
- Door locks

OPTIONAL ACCESSORIES

- Low Profile casters kit
- 1.5" caster, 1/2" diameter & 13 TPI: CAS1NBST00CC(non-brake), CAS1WBST00CC(w /brake)
- 1" drain pan: SDP1Q000
- Brackets for drain pan: (Left) SDP1Q000-BL, (Right) SDP1Q000-BR
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)

(GEAMAN) |KNIFE)

- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Removable food cover: RCT-28-12

Ver.20230112



Turbo air


■ Warranty : 800-381-7770 ■ AC : 888-900-1002

Turbo Air : 800-627-0032 **GK** : 800-500-3519


Texaking

PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

Continued product development may necessitate specification changes without notice.

Turbo air