

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Sandwich / Salad Unit - Drawers

Food Prep Tables PRO Series

Model: PST-28-D2-N

___ FEATURES & BENEFITS =__

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a 22 gauge stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

- Easy removable hood & hood lid for cleaning
- Insulated hood & hood lid
- Refrigerator holds 33°F ~ 39°F for the best in food preservation
- Lifetime guaranteed heavy duty handles
- Built to maintain NSF standard temperatures in 100°F ambient



Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Each top drawer accommodates up to 6" deep, one (1) full size pan with three (3) 1/6 size pan or three (3) 1/3 size pans with three (3) 1/6 size pan or nine (9) 1/6 size pans. And each bottom drawer accommodates up to 6" deep, one (1) full size pan or two (2) 1/3 size pans with two (2) 1/6 size pans or six (6) 1/6 size pans (drawer pans not included)













Model	Swing Doors	Drawers	CU./FT.	#of Shelves	#of Pans	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
PST-28-D2-N	-	2	7	ı	8	1/6	6.6	216	27 _{1/2} x 30 x 37 _{5/8}

(unit: inch)

Sandwich / Salad Unit - Drawers

Model: PST-28-D2-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	NEMA 5-15P				
Full Load Amperes	6.6				
Compressor HP	1/6				
Cord Length (ft.)	10				
Refrigerant	R-290				
DIMENSIONAL DATA					
Ext. Length Overall (in.)	271/2 (700mm)				
Ext. Depth Overall (in.)*	30 (762mm)				
Ext. Height Overall (in.)†	375/8 (955mm)				
# of Doors	-				
# of Drawers	2				
# of Shelves	-				
# of Pans	8				
# of Hood	1				
Net Capacity (cu. ft.)	7				
Net Weight (lbs.)	210				
Gross Weight (lbs.)	216				

Design and specifications subject to change without notice

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for drawer handles & rear spacers.

† Height does not include 4-1/2" for caster height.

5 Year Parts and Labor Warranty 7 Year Compressor Warranty

STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system
- 4" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included (top of cabinet)

OPTIONAL ACCESSORIES

· Low Profile casters kit

(4) 1" caster (Roller Type): S28R813660

(1) 3/8"H drain pan: SDP1Q000

(1) Brackets for drain pan: (Left) SDP1Q000-BL, (Right) SDP1Q000-BR


• 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)


• 6" ABS plastic leg: 30221M0200

• 6" stainless steel leg: 30221M0600

• Removable food cover: RCT-28

PLAN VIEW





Ver.20240726











■ **Turbo Air**: 800-627-0032 ■ **Radiance**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002





