

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

# Mega Top Unit - Slide Back Lid

### \_\_\_\_ FEATURES & BENEFITS =\_\_\_

#### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Digital temperature control & monitor system

Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

#### Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

#### Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a 22 gauge stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

#### Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. Only the PRO series uniquely provides stainless steel shelving.

High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using

high density, CFC free polyurethane insulation.

#### LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

#### Removable insulated slide-back lid


Removable hood and slide-back lid are easy to clean while providing a better view of the top opening.

# Model: PST-48-18-N-SL

Food Prep Tables **PRO** Series



#### Patented Self-Cleaning Condenser



- Spring assisted heavy duty gravity hinge
- Refrigerator holds 33°F ~ 39°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles
- Built to maintain NSF standard temperatures in 100°F ambient

 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail

Refrigerant U. S. A								
Model	Swing Doors	CU./FT.	#of Shelves	#of Pans	HP	AMPS	Crated Weight (lbs.)	$L \underset{(inches)}{x D^{*}x H^{\dagger}}$
PST-48-18-N-SL	2	15	2	18	1/5	6.5	268	481/4 x 34 x 39

Ver 20230815 Printed in U.S.A.

\* Depth does not include 3" for cutting board and 1" for rear spacers. † Height does not include 5" for caster height.

# Mega Top Unit - Slide Back Lid

## Model : PST-48-18-N-SL

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	<b>NEMA 5-15P</b>			
Full Load Amperes	6.5			
Compressor HP	1/5			
Cord Length (ft.)	10			
Refrigerant	R-290			
DIMENSIONAL DATA				
Ext. Length Overall (in.)	481/4 (1225mm)			
Ext. Depth Overall (in.)*	34 (864mm)			
Ext. Height Overall (in.) <sup>+</sup>	39 (992mm)			
# of Doors	2			
# of Shelves	2			
# of Pans	18			
# of Hood	1			
Net Capacity (cu. ft.)	15			
Shelf Size (L x D) (in.)	21 x 17			
Net Weight (lbs.)	259			
Gross Weight (lbs.)	268			

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 3" for cutting board and 1" for rear spacers.

† Height does not include 5" for caster height.

#### • WARRANTY : <sup>5</sup> Year Parts and Labor Warranty 7 Year Compressor Warranty

#### STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included
- \* Accommodates 1/6 size, 6" deep condiment pans
- Door locks

#### OPTIONAL ACCESSORIES


- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake),
- 30265H0200 (w/ brake) • 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600


Turbo air

- Single overshelf, stainless steel, 48-3/8" W: TSOS-4S
- Double overshelf, stainless steel, 48-3/8" W: TSOS-4R-T



(unit : inch)





Turbo air



(GEAMAN) KNIFE

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- **Warranty** : 800-381-7770 **AC** : 888-900-1002

Texaking

Continued product development may necessitate specification changes without notice.

Ver 20230815