

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA #:	SIS #:	
CSI Section 11400		

Worktop Refrigerator

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust and a rotating brush that moves up and down daily to remove excess buildup outward and away.

Model: PWR-48-N

Worktops PRO Series



🚐 FEATURES & BENEFITS 🚞

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a 22 gauge stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. Only the PRO series uniquely provides stainless steel shelving.

LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Spring assisted heavy duty gravity hinge
- Refrigerator holds 33°F ~ 38°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles
- Built to maintain NSF standard temperatures in 100°F ambient

PWR-48-N	2	12.2	2	1/6	6.5	285	481/4 x 30 x 335/8
Model	Swing Doors	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)
					Refrige	rant Intertek Interte	(U.S.A only)

Ver.20210603 Printed in U.S.A.

*Depth does not include 2" for door handles & rear spacers, † Height does not include 5" for caster height.

Worktop Refrigerator

Model: PWR-48-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	6.5				
Compressor HP	1/6				
Cord Length (ft.)	10				
Refrigerant	R-290				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	12.2				
Ext. Length Overall (in.)	481/4 (1225mm)				
Ext. Depth Overall (in.)*	30 (762mm)				
Ext. Height Overall (in.) [†]	335/8 (853mm)				
# of Doors	2				
# of Shelves	2				
Shelf Size (L x D) (in.)	21 x 17				
Net Weight (lbs.)	238				
Gross Weight (lbs.)	285				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for door handle & rear spacers.

+ Height does not include 5" for caster height.

WARRANTY: 3 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor

STANDARD FEATURES


- Anti-corrosion coated evaporator
- · Self-contained system
- · Standard 4" dia. swivel casters with locks on the front set
- Door locks standard
- ** Lead time applies. Please contact your sales representative for more details to order.

OPTIONAL ACCESSORIES


- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600


Turbo air

• Double overshelf, 18/304 stainless steel, 48-1/8" W: TSOS-4R



PLAN VIEW







Ver.20210603



(GERMAN

KNIFE)

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002

Texaking

515/8(1313mm) 527/8(1342mm)

(unit : inch)

PRO Series

Worktops

Continued product development may necessitate specification changes without notice.

Turbo air