

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

	Qty:
SIS #:	
	SIS#:

Chef Base Refrigerator (Extended Top)

Chef Bases Super Deluxe Series

Model: TCBE-36SDR-E-N6

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



= FEATURES & BENEFITS ==_

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing

■ Hydrocarbon refrigerants (R-600)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

- Strong body and durable construction Built with heavy duty 16 ga. stainless steel, Chef Base top is manufactured of one-piece reinforced stainless steel to ensure durability.
- Digital temperature display on front panel
- Each drawer accommodates up to 6" deep one (1) full size and three (3) 1/6 size pans (drawer pans not included)

- Top is insulated to eliminate heat transfer to the interior of cabinet
- Countertops

TCBE-36SDR-E-N6/48/52SDR-E-N supports up to 788 pounds of equipment. TCBE-72/82SDR-E-N supports up to 1,192 pounds of equipment.

- Durable stainless steel drawers
- Side mount compressor unit

Compressors positioned on the side of the units makes servicing our units easy. Our innovative, front breathing feature also allows this model to be highly efficient in narrow spaces.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Refrigerator holds 33°F ~ 38°F for the best in food preservation











Model	Drawers	CU./FT.	Countertop Weight Capacity (lbs.)	HP	AMPS	Crated Weight (lbs.)	L x D [*] x H [†] (inches)
TCBE-36SDR-E-N6	2	4.98	788	1/5	2.8	251	415/8 x 32 x 201/4

(unit: inch)

Model: TCBE-36SDR-E-N6

ELECTRICAL DATA	CTRICAL DATA		
Voltage	115/60/1		
Plug Type	NEMA 5-15P		
Full Load Amperes	2.8		
Compressor HP	1/5		
Cord Length (ft.)	9		
Refrigerant	R-600a		
DIMENSIONAL DATA			
Ext. Length Overall (in.)	415/8 (1057mm)		
Ext. Depth Overall (in.)*	32 (815mm)		
Ext. Height Overall (in.)†	201/4 (513mm)		
# of Drawers	2		
Net Capacity (cu. ft.)	4.98		
Net Weight (lbs.)	185		
Gross Weight (lbs.)	251		

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

- * Depth does not include 1" for rear spacers.
- † Height does not include 5" for caster height.

■ WARRANTY: 3 Year Parts and Labor Warranty
Additional 4 Year Warranty on Compressor

STANDARD FEATURES


- · Anti-corrosion coated evaporator
- · Self-contained system
- · 4" dia. swivel casters standard

OPTIONAL ACCESSORIES


• 6" stainless steel leg: 30221M0600

PLAN VIEW


* Each drawer accommodates up to 6" deep full size pans (drawer pans not included)



TOP VIEW



FRONT VIEW



SIDE VIEW

Ver 20210517













■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519









