

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA #:	SIS #:	
CSI Section 11400		

# Swing Door Freezers



## Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

## Digital temperature control & monitor system

- · Keeps food products safe by maintaining constant temperatures • Alarms that sound when doors are not sealed shut; protect against food
- spoilage that originate from cold air leaks · Early Warning Alarm program detect issues before malfunction occurs
- Digital display allows for easy monitoring
- · Programs interpret the condition of refrigeration systems by self-diagnosis
- Rapid cool-down function (Turbo freeze)
- · Smart defrost system will defrost as needed
- Automatic evaporator fan motor delays

#### Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

### Energy conserving fan control

Utilizing algorithmic air circulation for optimal temperature levels, our innovative fan control system conserves energy by at least 15% and increases compressor life by up to 30%.

#### No electrical cabinet heater is needed

Turbo Air is the first in the industry to replace a frame heater with a method of using compressor-produced heat. This eliminates any unnecessary energy consumption while providing efficient freezing performance.

#### High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

#### Triple pane heated glass doors

Equipped with unique triple-pane heated glass doors which enhance energy efficiency by preventing heat transfers and minimizing condensation. Lightweight door construction reduces door maintenance, bushing wear, and facilitates smooth door opening.

LED interior lighting


## Freezer holds -10°F ~ 5°F for the best in frozen food preservation

**Glass Door Merchandisers** Super Deluxe Series

# Model : TGF-23SDH\*-N



TGF-23SDHB-N





This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

				N. Re	Swigowant	9001:2008 Intertek Inter	(USA only) Qualified
Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^{\dagger}$
TGF-23SDH*-N	1	17.9	4	1/2	5.8	365	27 x 301/4 x 77

Ver.20240624 Printed in U.S.A.

\*Depth does not include 2-1/4" (57mm) for door handle. † Height does not include 2-1/2" (63mm) for leg height. ‡ White cabinet (W), Black cabinet (B).

# Swing Door Freezers

# Model : TGF-23SDH\*-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	<b>NEMA 5-15P</b>				
Full Load Amperes	5.8				
Compressor HP	1/2				
Cord Length (ft.)	7				
Refrigerant	R-290				
DIMENSIONAL DATA					
# of Doors	1				
Net Capacity (cu. ft.)	17.9				
Ext. Length Overall (in.)	27 (685mm)				
Ext. Depth Overall (in.)*	301/4 (771mm)				
Ext. Height Overall (in.) <sup>†</sup>	77 (1956mm)				
Int. Length Overall (in.)	23 (585mm)				
Int. Depth Overall (in.)	251/4 (641mm)				
Int. Height Overall (in.)	521/4 (1328mm)				
# of Shelves	4				
Shelf Size (L x D) (in.)	<b>21</b> 1/2 <b>x 22</b> 1/2				
Net Weight (lbs.)	343				
Gross Weight (lbs.)	365				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 2-1/4" (57mm) for door handle. † Height does not include 2-1/2" (63mm) for leg height.

# 5 Year Parts and Labor Warranty 7 Year Compressor Warranty WARRANTY :

## STANDARD FEATURES

- Anti-corrosion coated evaporator
- Adjustable PE (polyethylene) coated wire shelves
- Door locks
- \* Two color options available (standard): white cabinet (W), black cabinet with black color trim (B).

#### OPTIONAL ACCESSORIES

SPEC

NATURAL

Refrigerant

- 4" caster, 1/2" diameter & 13 TPI: 30265L0400 (non-brake), 30265L0300 (w/ brake)
- Additional PE coated wire shelf: 30278R0102

Intertek

Intertek

5 YEAR


lurbo air

7 YEAR WARRANTY

• Price tag channel: P0122K5100 (20-1/4"L)

# **PLAN VIEW**

(unit : inch)



Ver 20240624

ENERGY STAR® Qualified

**Turbo Air:** 800-627-0032 **Radiance:** 800-500-3519

Texaking

■ Warranty: 800-381-7770 ■ AC: 888-900-1002

Continued product development may necessitate specification changes without notice.

lurbo air