

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:	(Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Worktop Refrigerator - Drawers

Worktops Super Deluxe Series

Model: TWR-48SD-D2-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



== FEATURES & BENEFITS ==_

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Digital temperature control & monitor system Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

Ergonomically designed door

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Each drawer accommodates up to 6" deep, two (2) 1/3 size pans or four (4) 1/6 size pans (drawer pans not included)
- Refrigerator holds 33°F ~ 38°F for the best in food preservation









Model	Swing Doors	Drawers	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
TWR-48SD-D2-N	1	2	12	1	1/5	2.4	264	481/4 x 30 x 335/8

(unit: inch)

Model: TWR-48SD-D2-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	(i) NEMA 5-15P			
Full Load Amperes	2.4			
Compressor HP	1/5			
Cord Length (ft.)	9			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	12			
Ext. Length Overall (in.)	481/4 (1225mm)			
Ext. Depth Overall (in.)*	30 (762mm)			
Ext. Height Overall (in.)†	335/8 (853mm)			
# of Doors	1			
# of Drawers	2			
# of Shelves	1			
Shelf Size (L x D) (in.)	21 x 17			
Net Weight (lbs.)	242			
Gross Weight (lbs.)	264			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

5 Year Parts and Labor Warranty 7 Year Compressor Warranty WARRANTY:


STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system
- 4" dia. swivel casters with locks on the front set
- · Magnetic door and drawer gaskets


OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Double overshelf, 18/304 stainless steel, 48-1/8" W: TSOS-4R

PLAN VIEW



TOP VIEW



SIDE VIEW

Ver.20230119










■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519













^{*} Depth does not include 1" for rear spacers

[†] Height does not include 5-5/8" for caster height.