

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Pass Thru Glass & Solid Door Heated Cabinet

Pass-Thru PRO Series

Model: PRO-50H-GS-PT

PRO-50H-SG-PT

___ FEATURES & BENEFITS =__

■ Digital temperature control & monitor system

- Keeps food products safe by maintaining constant temperatures
- · Alarm beeps when doors are not sealed
- Early warning alarm program detects issues before malfunction occurs
- Digital display allows for easy monitoring
- · Sensitive touch display

Ducted fan air distribution system

Maintains temperature within the food zone

On/Off switch

ON/OFF switch is located on control panel

All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a 22 gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ LED interior lighting

Includes a U.S. patented dimming option, exclusively from Turbo Air. This feature reduces energy consumption by 3~5%.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Full length glass doors (stainless steel soild doors) with locks

- Self-closing doors with stay open feature at 120 degrees
- Heated cabinet holds 140°F ~ 180°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles
- PRO-50H-GS-PT: (Front)Glass + (Back)Solid Door
- PRO-50H-SG-PT: (Front)Solid + (Back)Glass Door











PRO-50H-GS(SG)-PT	4	48.7	6	3000	15	500	513/4 x 361/4 x 78
Model	Swing Doors	CU./FT.	#of Shelves	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)

(unit: inch)

Model: PRO-50H-GS(SG)-PT

ELECTRICAL DATA				
Voltage	208/115/60/1			
Plug Type	○ NEMA L14-20P			
Full Load Amperes	15			
Wattage (W)	3000			
Cord Length (ft.)	8			
DIMENSIONAL DATA				
# of Doors	4			
# of Racks Accepted	2			
Net Capacity (cu. ft.)	48.7			
Ext. Length Overall (in.)	513/4 (1314mm)			
Ext. Depth Overall (in.)*	361/4 (920mm)			
Ext. Height Overall (in.)†	78 (1982mm)			
Int. Length Overall (in.)	421/4 (1073mm)			
Int. Depth Overall (in.)	273/4 (703mm)			
Int. Height Overall (in.)	58 _{3/4} (1493mm)			
# of Shelves	6			
Shelf Size (L x D) (in.)	223/4 x 263/8			
Net Weight (lbs.)	442			
Gross Weight (lbs.)	500			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty


STANDARD FEATURES


- Door locks
- · 4" dia. swivel casters with locks on the front set
- · Easy replaceable one piece magnetic door gaskets
- · Solid and sturdy grille design

OPTIONAL ACCESSORIES

- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: (L, R) H50R901700
- · Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans)
- Full door bun tray rack: TSP-2250 (each holds up to fifteen 18"L x 26"D sheet pans)
- Tray slides kits: TS23-N1LR(#1), TS23-N1LR HALF, TS23-N4LR(#4), TS23-N4LR HALF, TS23-UNLR-H(Universal), TS23-UNLR-H HALF
- (1) Pair of #1 Tray Slides: H26R104460
- (1) Pair of Universal Tray Slides: H26R104470

PLAN VIEW





Ver 20230126














■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Depth does not include 2-1/2" for door handles.

[†] Height does not include 4-3/4" for caster height.