

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

# Solid Door Heated Cabinet - For Correctional Facility

Reach-In PRO Series

Model: PRO-50H-CRT

## \_\_\_ FEATURES & BENEFITS =\_\_

#### Digital temperature control & monitor system

- Keeps food products safe by maintaining constant temperatures
- · Alarm beeps when doors are not sealed
- · Early warning alarm program detects issues before malfunction occurs
- · Digital display allows for easy monitoring
- · Sensitive touch display

#### Ducted fan air distribution system

Maintains temperature within the food zone

#### On/Off switch

ON/OFF switch is located on control panel

#### All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a 22 gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

#### Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

#### ■ LED interior lighting

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

### Full length stainless steel solid doors with locks

#### Self-closing doors with stay open feature at 120 degrees

#### Corrections - ready features

Our PRO series CRT units come fully equipped with all the required correctional facilities' features. It includes the stainless steel light cover with security screws, stainless steel PCB cover with security screws, hinges without covers, stainless mesh cover on top, locking hasp (padlock not included), tray slide with security screws and flanged leg.

#### ■ Heated cabinet holds 140°F ~ 180°F for the best in food preservation

#### Lifetime guaranteed heavy duty hinges and handles











PRO-50H-CRT	2	47.7	6	3000	15	472	513/4 x 337/8 x 78
Model	Swing Door	CU./FT.	#of Shelves	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D*x H † (inches)

(unit: inch)

# **Model: PRO-50H-CRT**

ELECTRICAL DATA				
Voltage	208/115/60/1			
Plug Type	NEMA L14-20P			
Full Load Amperes	15			
Wattage (W)	3000			
Cord Length (ft.)	8			
DIMENSIONAL DATA				
# of Doors	2			
# of Racks Accepted	2			
Net Capacity (cu. ft.)	47.7			
Ext. Length Overall (in.)	513/4 (1314mm)			
Ext. Depth Overall (in.)	337/8 (861mm)			
Ext. Height Overall (in.)*	78 (1982mm)			
Int. Length Overall (in.)†	421/4 (1073mm)			
Int. Depth Overall (in.)	275/8 (702mm)			
Int. Height Overall (in.)	583/4 (1493mm)			
# of Shelves	6			
Shelf Size (L x D) (in.)	223/4 x 263/8			
Net Weight (lbs.)	419			
Gross Weight (lbs.)	472			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

#### ■ WARRANTY: 3 Year Parts and Labor Warranty


#### STANDARD FEATURES


- Door locks
- · Easy replaceable one piece magnetic door gaskets
- · Solid and sturdy grille design
- \*\* Lead time applies. Please contact your sales representative for more details to order.

#### OPTIONAL ACCESSORIES

- · Additional stainless steel shelf: (L, R) H50R901700
- Half door bun tray rack: TSP-2224 (each holds up to six 18"L x 26"D sheet pans)
- Full door bun tray rack: TSP-2250 (each holds up to fifteen 18"L x 26"D sheet pans)
- Tray slides kits: TS23-N1LR(#1), TS23-N1LR HALF, TS23-N4LR(#4), TS23-N4LR HALF, TS23-UNLR-H(Universal), TS23-UNLR-H HALF
- (1) Pair of #1 Tray Slides: H26R104460
- (1) Pair of Universal Tray Slides: H26R104470

# **PLAN VIEW**





Ver.20220713

















■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002

<sup>\*</sup> Depth does not include 1-1/4" for door handles.

<sup>†</sup> Height does not include 4-3/4" for leg height.