

 <b>REFRIGERATOR MANUFACTURER</b> <b>Turbo air</b> more durable, efficient, beautiful	4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 <a href="http://www.turboairinc.com">www.turboairinc.com</a>	Project:	
		Model #:	
		Item #:	
		Available W/H:	Qty:
		Approval:	
		AIA #:	SIS #:
		CSI Section 11400	

**Roll-In Solid Door Heated Cabinet - For Correctional Facility** *Reach-In PRO Series*

**Model : PRO-50H-RI-CRT**

**FEATURES & BENEFITS**


- **Digital temperature control & monitor system**

  - Keeps food products safe by maintaining constant temperatures
  - Alarm beeps when doors are not sealed
  - Early warning alarm program detects issues before malfunction occurs
  - Digital display allows for easy monitoring
  - Sensitive touch display
- **Ducted fan air distribution system**  
Maintains temperature within the food zone
- **Corrections - ready features**  
Our PRO series CRT units come fully equipped with all the required correctional facilities' features. It includes the stainless steel light cover with security screws, stainless steel PCB cover with security screws, hinges without covers, stainless mesh cover on top, locking hasp (padlock not included), tray slide with security screws and flanged leg.
- **On/Off switch**  
ON/OFF switch is located on control panel
- **All stainless steel cabinet construction**  
The PRO series model boasts a stainless steel interior and a **22 gauge** stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.
- **LED interior lighting**
- **High-density polyurethane insulation**  
The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- **Full length stainless steel solid doors with locks**
- **Self-closing doors with stay open feature at 120 degrees**
- **Heated cabinet holds 140°F ~ 180°F for the best in food preservation**
- **Lifetime guaranteed heavy duty hinges and handles**



Model	Swing Door	CU./FT.	#of Rack Accepted	Wattage (W)	AMPS	Crated Weight (lbs.)	L x D <sup>*</sup> x H <sup>†</sup> (inches)
<b>PRO-50H-RI-CRT</b>	<b>2</b>	<b>75.6</b>	<b>2</b>	<b>3000</b>	<b>15</b>	<b>816</b>	<b>667/8 x 373/4 x 841/4</b>

## Model : PRO-50H-RI-CRT

ELECTRICAL DATA	
Voltage	208/115/60/1
Plug Type	 NEMA L14-20P
Full Load Amperes	15
Wattage (W)	3000
Cord Length (ft.)	8
DIMENSIONAL DATA	
# of Doors	2
# of Rack Accepted (Size (L x D x H) (in.))	2 (27 x 29 x 66)
Net Capacity (cu. ft.)	75.6
Ext. Length Overall (in.)	667/8 (1700mm)
Ext. Depth Overall (in.)	373/4 (960mm)
Ext. Height Overall (in.)*	841/4 (2140mm)
Int. Length Overall (in.)	573/8 (1459mm)
Int. Depth Overall (in.)	311/2 (800mm)
Int. Height Overall (in.)	667/8 (1700mm)
Net Weight (lbs.)	758
Gross Weight (lbs.)	816

Design and specifications subject to change without notice.  
Actual shipping weight may differ due to extra packing materials for product protection.  
\* Depth does not include 1-1/4" for door handles. Depth does not include 3-1/2" for ramps.

### ■ WARRANTY : 3 Year Parts and Labor Warranty



### ■ STANDARD FEATURES

- Door locks
- Solid and sturdy grille design
- Heavy duty stainless steel ramp

\*\* Lead time applies. Please contact your sales representative for more details to order.

## PLAN VIEW

(unit : inch)



Ver.20220713



- Turbo Air : 800-627-0032
- GK : 800-500-3519
- Warranty : 800-381-7770
- AC : 888-900-1002

REFRIGERATOR MANUFACTURER  
**Turbo air**

GERMAN  
KNIFE

RADIANCE

REFRIGERATION SYSTEM  
**Turbo air**

**TEXAKING**

Continued product development may necessitate specification changes without notice.