

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
tem #:		
Available W/H:		Qty:
Approval:		
AIA #:	SIS #:	
CSI Section 11400		

Undercounter Freezer - Drawers

Patented Self-Cleaning Condenser



Model : TUF-60SD-D2R-N

Undercounters

Super Deluxe Series



____ FEATURES & BENEFITS ≡

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system Keeps food products safe by maintaining constant temperatures.

External digital display allows for easy monitoring.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Magnetic door gaskets

Magnetic door gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

- Each drawer accommodates up to 6" deep, one (1) full size pan or three (3) 1/3 size pans or six (6) 1/6 size pans (drawer pans not included)
- Freezer holds -10°F ~ 0°F for the best in frozen food preservation

Г

							rigerant	Intertek
Model	Swing Doors	Drawers	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (Ibs.)	$L \ge D^* \ge H^+$ (inches)
TUF-60SD-D2R-N	1	2	17.2	1	1/2	8.0	288	601/4 x 30 x 30

Ver.20230815 Printed in U.S.A.

* Depth does not include 1" for rear spacers, + Height does not include 5" for caster height.

Undercounter Freezer - Drawers

Model: TUF-60SD-D2R-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	NEMA 5-15P			
Full Load Amperes	8.0			
Compressor HP	1/2			
Cord Length (ft.)	10			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	17.2			
Ext. Length Overall (in.)	601/4 (1530mm)			
Ext. Depth Overall (in.)*	30 (762mm)			
Ext. Height Overall (in.) [†]	30 (762mm)			
# of Doors	1			
# of Drawers	2			
# of Shelves	1			
Shelf Size (L x D) (in.)	27 x 17			
Net Weight (lbs.)	250			
Gross Weight (lbs.)	288			

Design and specifications subject to change without notice Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1" for rear spacers.

† Height does not include 5" for caster height.


5 Year Parts and Labor Warranty 7 Year Compressor Warranty **WARRANTY**:

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters with locks on the front set

OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Back splash guard: TU-60B
- · Single overshelf, stainless steel, 60-3/8" W: TSOS-5S
- Double overshelf, stainless steel, 60-3/8" W: TSOS-5R-T



Ver.20230815



lurbo air

Turbo Air : 800-627-0032 **GK** : 800-500-3519

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

(GERMAN Texaking Turbo air KNIFE Continued product development may necessitate specification changes without notice.